

## Storm-Resistant Design Helps Save Lives



**Top Latch**  
5/8" stainless steel  
housings, 3/4" projection  
with 1/8" window gap



**Center Bolt**  
Stainless steel deadbolt  
with 1" projection



**Bottom Bolt**  
3/4" diameter steel with  
3/4" projection



**Center Bolt Strike**  
1/4" stainless steel strike  
versus 1/8" standard  
wrought strike

### Storm Shutter Multi-Point Latching System for Window Openings

The Corbin Russwin FE6700 is a robust three-point locking system engineered to help save lives by securing the community shelter window openings. Extra heavy-duty steel components secure the shutter to the frame – at the top, bottom and center latch points – fortifying the opening to withstand extreme wind speeds and flying debris. UL approved, the FE6700 is ideal for both FEMA 361 and ICC 500.

To learn more about the FE6700 and how Corbin Russwin can help you keep people safe and secure, call 800-543-3658 or visit [corbinrusswin.com](http://corbinrusswin.com).



# FE6700

## Storm Shutter Multi-Point Latching System

**Community Refuge Area Shutter Hardware**  
For use with UL approved shutter assemblies\* that comply to FEMA 361 and ICC 500.

### Applications

FE6700 is ideal for window openings located in:  
Community Shelters and Safe Rooms, Corporate Campuses,  
Schools, Healthcare Facilities, Government Facilities

### Features & Benefits

- < Three point auto deadlocking system
- < UL approved to FEMA 361 and ICC 500
- < In swing applications
- < Heavy duty escutcheons standard
- < Fully Integrated - FE6700 is part of a complete ASSA ABLOY severe windstorm solution utilizing Ceco StormPro® 361, Curries StormPro® 361 and Fleming F-5 shutters and frames and McKinney hinges.
- < Fortified with high tensile alloy Holo-Krome® fasteners.
- < All three latching points are activated automatically when the shutter is closed.

\*For the latest listings on compliant shutter assemblies visit our website at [corbinrusswin.com](http://corbinrusswin.com)

### For Typical Shutter Applications

Outside   Inside	Series/ Function	Type	Function Description
	FE6780	Passage Lever x Blank Plate	<ul style="list-style-type: none"> <li>• Three-point auto deadlocking.</li> <li>• Three-point latch retraction by inside grip.</li> <li>• Lever on one side, blank plate on the other.</li> <li>• Lever always free.</li> <li>• For inswing window storm shutters.</li> </ul>

### Optional Functions

Outside   Inside	Series/ Function	Type	Function Description
	FE6755	Classroom	<ul style="list-style-type: none"> <li>• Three-point auto deadlocking.</li> <li>• Three-point latch retraction by grip either side, unless outside grip is locked by key outside.</li> <li>• Inside grip always free.</li> </ul>
	FE6710	Passage or Closet	<ul style="list-style-type: none"> <li>• Three-point auto deadlocking.</li> <li>• Three-point latch retraction by grip either side.</li> <li>• Both grips always free.</li> </ul>

