



Hurricane Certification Listings



Hurricane Certification	Product Series	Model #	Statewide Florida Product Approval	Door Configuration	Maximum Opening Size	Door Stiffness Class (min)	Design Load (psf)	Impact (ft-lbs)	Latch Throw Min (in.)	Latch Strength Min (lbf)
UL-ZHEM.R21801	Mortise Locks	8800 series	FL11527	Single	3-0 x 7-0	I	*/- 50	350	3/4"	525
		8800 series	FL6226	Single	3-0 x 7-0	I	*/- 60	350	3/4"	630
		8800 series (latchbolt x deadbolt)	FL3063	Single inswing or outswing	3-0 x 7-0	I	*/- 115	350	3/4"	1208
		8800 series (latchbolt x deadbolt)	FL3063	Single - deadbolt and latchbolt engaged	4-0 x 8-0	I	*/- 70	350	3/4"	1120
		8800 series (latchbolt x deadbolt)	FL6226	Paired - deadbolt and latchbolt engaged with (2) 988Y surface bolts engaged (inactive leaf)	8-0 x 8-0	I	*/- 70	350	3/4"	1120
	Cylindrical Locks	4600LN series	FL11527	Single	3-0 x 7-0	I	*/- 50	350	1/2"	525
		4700LN series	FL11527	Single	3-0 x 7-0	I	*/- 50	350	1/2"	525
		5400/5400LN series	FL6226	Single inswing	3-0 x 7-0	I	*/- 60	350	1/2"	630
		5400/5400LN series with D100 series deadbolt	FL6226	Single inswing - deadbolt and latchbolt engaged	3-0 x 7-0	I	*/- 70	350	1/2"	735
		4800LN series interconnected	FL6226	Single inswing - deadbolt and latchbolt engaged	3-0 x 7-0	I	*/- 70	350	1/2"	735
		e4760LN series inTouch™	—	Single	3-0 x 7-0	I	*/- 50	350	1/2"	525
		e5360LN series inTouch™	—	Single	3-0 x 7-0	I	*/- 60	350	1/2"	630
	Exit Devices and Mullions	7150(F)WS	FL3063	Single outswing	3-0 x 7-0	I	*/- 60	350	3/4"	630
		7150(F)WS	FL3063	Single outswing	3-0 x 7-0	I	*/- 115	350	3/4"	1208
		7150(F)WS	FL3063	Single outswing	4-0 x 8-0	I	*/- 70	350	3/4"	1120
		7150(F)WS	FL3063	Paired outswing - with M200FWS or KRM200FWS mullions	8-0 x 8-0	I	*/- 70	350	3/4"	1120
		7250M(F)WS	FL3063	Single outswing	3-0 x 7-0	I	*/- 115	350	3/4"	1208
		7250M(F)WS	FL3063	Single outswing	4-0 x 8-0	I	*/- 70	350	3/4"	1120
		7250M(F)WS	FL3063	Paired outswing - with M200FWS or KRM200FWS mullions	8-0 x 8-0	I	*/- 70	350	3/4"	1120
		7170(F)WS	FL3063	Single outswing	4-0 x 8-0	I	*/- 70	350	3/4"	1120
7170(F)WS		FL3063	Paired outswing	8-0 x 8-0	I	*/- 70	350	N/A	N/A	
2100(F)WS		FL11527	Single	3-0 x 7-0	I	*/- 50	350	3/4"	525	



Hurricane Certification Listings



Hurricane Certification	Product Series	Model #	Statewide Florida Product Approval	Door Configuration	Maximum Opening Size	Door Stiffness Class (min)	Design Load (psf)	Impact (ft-lbs)	Latch Throw Min (in.)	Latch Strength Min (lbf)
UL-ZHEM.R21801	Multi-Point Locks	7380F Series	FL12704	Single	4-0 x 8-0	I	*/- 150	350	3/4"	800
		7380F Series	FL12704	Pair - with (2) 988Y surface bolts engaged (inactive leaf)	8-0 x 8-0	I	*/- 150	350	3/4"	800
	Surface Bolt	988Y	FL12704	Paired	8-0 x 8-0	I	*/- 150	350	N/A	1200
Test Report	Mortise Locks	8800 series (latchbolt x deadbolt)	FL4342	Single inswing - deadbolt and latchbolt engaged	3-0 x 7-0	I	*/- 60	350	3/4"	735
		8800 series with or without Securitron EPTL power transfer	FL4342	Single	3-0 x 7-0	I	*/- 60	350	3/4"	630
		8800 series with or without Securitron MUNL unlatch electromechanical strike	FL4342	Single	3-0 x 7-0	I	*/- 60	350	3/4"	630
		e8800FL series eBoss®	FL4342	Single	3-0 x 7-0	I	*/- 60	350	3/4"	630
	Cylindrical Locks	5300/5300LN series	FL4342	Single inswing	3-0 x 7-0	I	*/- 60	350	1/2"	630
		5400/5400LN series with or without Securitron UNL unlatch electromechanical strike	FL4342	Single	3-0 x 7-0	I	*/- 60	350	1/2"	630
		e5400LN series eBoss®	FL4342	Single	3-0 x 7-0	I	*/- 60	350	1/2"	630
Evaluation Report	Exit Devices and Mullions	7250M(F)WS	FL13321	Paired outswing YKK Aluminum/Glass Storefront Assembly ONLY	7-0 x 8-0	N/A	*/- 60	350	3/4"	N/A

Yale Locks & Hardware • 225 Episcopal Road, Berlin, CT 06037-4004 • Tel: 1-800-438-1951 • Fax: 1-800-338-0965 • www.yalelocks.com

Yale Locks & Hardware is a division of Yale Security Inc., an ASSA ABLOY Group company.

Disclaimer: This is a comparison for like product. It is not a legal or binding document. Consult Mfg. Catalog for special detail and accuracy.

Yale® and eBoss® are registered trademarks of Yale Security Inc., an ASSA ABLOY Group company. inTouch™ is a trademark of Yale Security Inc., an ASSA ABLOY Group company. Other products' brand names may be trademarks or registered trademarks of their respective owners and are mentioned for reference purposes only. These materials are protected under U.S. copyright laws. All contents current at time of publication. The ASSA ABLOY Group companies reserve the right to change availability of any item in this catalog, its design, construction, and/or its materials. Copyright © 2011, 2013, Yale Security Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Yale Security Inc., an ASSA ABLOY Group company.

42761 - 3/13RE